



RM20 Radio Receiver Modules


Compact 4 output receiver. 2 Digital on/off and 2 configurable analog or digital



FEATURES

- **Compact Size**
Compact design with mounting tabs integrates easily into control panels.
- **Configurable Outputs**
2 x digital on/off outputs plus 2 x configurable outputs including PWM current, ratiometric, 0-10v, 4-20mA and digital on/off.
- **External antenna**
Replaceable "stubby" antenna for maximum range. Other antenna options also available including cabled versions.
- **Reliable communication**
2.4GHz and 900MHz models for long-range reliability. 433Mhz fixed frequency version also available for compatibility with economy transmitters.
- **Cost Effective**
Value priced, simple receiver for controlling up to four loads.

ORDERING INFORMATION




Output 3 and 4 are On/Off on all RM20 models.

SPECIFICATIONS

Power	Power Supply	12 to 24 VDC, 100mA max. plus load current
Outputs	RM20	4 outputs. Output 1 and 2 factory configurable.
	Output Capacity	3 amps max. per channel, 7 amps max total
Enclosure		Thermoplastic, 3" w x 2.75" h x 1" d, with molded-in mounting brackets

WIRING



Consult installation manual prior to installation or service.

		RANGE	
MODEL	FREQUENCY	INDOOR/URBAN	OUTDOOR LINE OF SIGHT
REM20	902-928MHz, FHSS	1,000'	Up to 3 miles with Yagi antenna
RNM20	902-928MHz, FHSS	300'	1,000'
RZM20	2.4GHz, DSSS	300'	1,000'
RFM20	433MHz, Fixed	30'	100'